

## Thermo Scientific Heraeus Primo and Primo R Centrifuges



Specifications	Heraeus Primo	Heraeus Primo R
<b>Drive</b>	Induction drive without carbon brushes	Induction drive without carbon brushes
<b>Control</b>	EASYcontrol® II microprocessor controlled	EASYcontrol II microprocessor controlled
<b>Max. speed</b>	rpm 15,000, adjustable in increments of 10	15,000, adjustable in increments of 10
<b>Min. speed</b>	rpm 300	300
<b>Max. RCF</b>	x g 21,885	21,885
<b>Max. capacity</b> (fixed angle rotor)	6 x 50 mL high-speed tubes 6 x 15/50 mL disposable conical	6 x 50 mL high-speed tubes 6 x 15/50 mL disposable conical
<b>Max. capacity</b> (swinging bucket rotor)	4 x 100 mL DIN 4 x 15/50 mL disposable conical 12 x 7/15 mL blood sample	4 x 100 mL DIN 4 x 15/50 mL disposable conical 12 x 7/15 mL blood sample
<b>Temperature range</b>	° C –	–9 to 40
<b>Braking/accel. curves</b>	9/2	9/2
<b>Noise level at max. speed</b>	< 62 dB	< 60 dB
<b>Run time</b>	0–9 hrs 59 mins, cont. operation (hold)	0–9 hrs 59 mins, cont. operation (hold)
<b>Functions</b>	RCF pre-selection, quick-run	RCF pre-selection, quick-run
<b>Rotor recognition</b>	Automatic	Automatic
<b>Imbalance recognition</b>	Electronic, ideally tuned for every rotor	Electronic, ideally tuned for every rotor
<b>Program memory</b>	The most recent data remains in the memory	The most recent data remains in the memory
<b>Construction</b>	Galvanized steel chassis with armored chamber and plastic outer casing	Galvanized steel chassis with armored chamber and plastic outer casing
<b>Centrifuge protection</b>	Lid lock and interlock	Lid lock and interlock
<b>Dimensions (H x W x D)</b>	mm (inch) 315 x 380 x 475 (12.4 x 15 x 16.7)	313 x 580 x 493 (12.3 x 22.8 x 15.3)
<b>Weight</b>	kg (lb) 40 (88)	69.5 (153)
<b>Power consumption</b>	W 350	490
<b>Test standards</b>	Manufactured and tested in accordance with EN 61 010-1, EN 61 010-2-020, EN 50 081-1, EN 50 082-1; UVV VBG 7z test is not required	Manufactured and tested in accordance with EN 61 010-1, EN 61 010-2-020, EN 50 081-1, EN 50 082-1; UVV VBG 7z test is not required

Ordering Information	Heraeus Primo	Heraeus Primo R
230 V, 50/60 Hz, excluding accessories	75005181	75005440
120 V, 50 Hz, excluding accessories	75005182	75005441

© 2008, 2011 Thermo Fisher Scientific Inc. All rights reserved. HERAEUS is a registered trademark of Heraeus Holding GmbH licensed to Thermo Fisher Scientific. All other trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

**North America:** USA/Canada +1 866 984 3766 (866-9-THERMO)

**Europe:** Austria +43 1 801 40 0, Belgium +32 53 73 42 41, France +33 2 2803 2180, Germany national toll free 08001-536 376, Germany international +49 6184 90 6940, Italy +39 02 95 05 92 54, Netherlands +31 76 579 55 55, Nordic/Baltic countries +358 9 329 10200, Russia/CIS +7 (812) 703 42 15, Spain/Portugal +34 93 223 09 18, Switzerland +41 44 454 12 12, UK/Ireland +44 870 609 9203

**Asia:** Australia +61 39757 4300, China +86 21 6865 4588 or +86 10 8419 3588, India toll free 1800 22 8374, India +91 22 6716 2200, Japan +81 45 453 9220, New Zealand +64 9 980 6700,

Other Asian countries +852 2885 4613 **Countries not listed:** +49 6184 90 6940

BRCFGHERPRIMO 0211

[www.thermoscientific.com/centrifuge](http://www.thermoscientific.com/centrifuge)

**Thermo**  
SCIENTIFIC