

Specifications and Ordering Information

PRISM SPECIFICATIONS

Speed Range	500 to 15,000 rpm
Maximum RCF	21,200 x g
Maximum Capacity	24 x 1.5/2.0 ml
Timer	0.5 to 99 minutes OR continuous "Quick" button for momentary operation
Temperature Range	N/A
Dimensions (WxDxH)	24 x 35 x 19 cm
Weight	21 lb (9.6 kg)
Electrical	120V~, 60Hz or 230V~, 50Hz

PRISM R SPECIFICATIONS

Speed Range	500 to 13,500 rpm
Maximum RCF	17,135 x g
Maximum Capacity	24 x 1.5/2.0 ml
Timer	0.5 to 99 minutes OR continuous "Quick" button for momentary operation
Temperature Range	-10 ^o -40 ^o C
Dimensions (WxDxH)	27.7 x 45 x 24.75 cm
Weight	44 lb (20 kg)
Electrical	120V~, 60Hz or 230V~, 50Hz

PRISM ORDERING INFORMATION

Catalog No.	Description
C2500*	Prism air-cooled microcentrifuge with 24 place rotor, 120V
C2500-R*	Prism R refrigerated microcentrifuge with 24 place rotor, 120V
C2400-SS	StripSpin™ adapter for 0.2 ml tubes and strips
C1205	Individual adapters for 0.5/0.6 ml tubes, pk of 6
C1206	Individual adapters for 0.4/0.25 ml tubes, pk of 6
C1222	Individual adapters for 0.2 ml thermal cycling tubes, pk of 6

* For 230V units, add -230V to the end of catalog number.

230V includes both EU and UK power cords.

